

(12) INTERNATIONAL LICATION PUBLISHED UNDER THE PATEN bperation treaty (c.t.) 540006

## (19) World Intellectual Property Organization International Bureau



(43) International Publication Date 17 June 2004 (17.06.2004)

PCT

(10) International Publication Number WO 2004/051013 A2

(31) International Patent Classification7:

E03D 5/00

(3) International Application Number:

PCT/US2003/038021

(22) International Filing Date:

26 November 2003 (26.11.2003)

(25) Filling Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/430,130

30 November 2002 (30.11.2002) US

- (71) Applicant (for all designated States except US): THET-FORD CORPORATION [US/US]; P.O. Box 1285, Ann Arbor, MI 48106 (US).

- (74) Agents: OLSON. Stephen T. et al.; Harness, Dickey & Pierce, P.L.C., P.O. Box 828, Bloomfield Hills, MI 48303 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,

(72) Inventors; and
(75) Inventors/Applicants (for US only); GRECH, George [US/US]; \* (US). KEITH, KIm [US/US]; \* (US). FRITZ, Michael [US/US]; \* (US). SMITH, Jason [US/US]; \* (US). EXPER, Greg [US/US]; \* (US). SMITH, Jason [US/US]; \* (US). MEYER, Steve [US/US]; \* (US). KARAGITZ, Craig [US/US]; \* (US). KRUPP, Eric [US/US]; \* (US).

(54) Title: REDUCED WATER CONSUMPTION FLUSH TOILET

(57) Abstract: A reduced water consumption flush toilet for a motor vehicle includes a bowl assembly, a waste ball valve assembly and a water valve assembly defines a bowl and a discharge opening at a lower end of the bowl. The water ball valve assembly is mounted to the flush toilet for selectively opening and closing the discharge opening of the bowl assembly. The water valve assembly is mounted to the flush toilet for selectively opening and closing the discharge opening of the bowl assembly. The water valve open condition and a water valve closed condition. The flush toilet further includes a water valve operable in a water valve open condition and a water valve assembly and the water valve assembly. The common actuator is movable from a first position to an intermediate position and from the intermediate position to a second position such that in the first position the waste ball valve assembly and the water valve assembly is in the closed condition. The first position the waste ball valve assembly and the water valve assembly is in the closed condition. closes the discharge opening and the water valve assembly is in the open position for adding water to the bowl, and in the second position the waste ball valve assembly opens the discharge opening and the water valve assembly is in the open position for flushing the bowl.

